

MOLECULAR - LUBRICANT

FAST RUST LOOSENER MLX spray

SOLVENT OF RUST

PRODUCT DESCRIPTION

High diffusible fine lubricant oil MLX has unique properties for all purposes. It is a high-performance product for quick loosening of rusted bolts, bars, locks etc..

MLX is a compound of very fine penetrants with a high lubricating grade (without MoS₂) having an long-lasting effect including anticorrosive prevention.

TYPICAL USE

Releases jammed joints. It is ideal for using on dead bolts, nuts, dead bearings, locks, friction bearings, pulls in bowdells, electric switches, timers, contacts, tools (pliers, scissors, bicycle chains).

It loosens joints, improves free-wheel and prevents against rust of locks, ears and chains.

It protects against rust of exposed surfaces.

PROPERTIES

- Very quick
- Reduces friction
- Clean - does not leave stains
- Contains no Molybdenum disulfid
- Protection against sudden jamming and locking of parts
- Provides a deeper penetration
- Little inclination to oxidation
- Protection against rust
- Does not affect rubber, the most of plastic materials, metals and non-ferrous metals though it should be tested.

FAST RUST LOOSENER MLX spray

TECHNICAL DATA

Colour : reddish
Composition : a compound of solvents, mineral oils and izomers
Content of solid substances: N/A
Viscosity : penetration - low
Odour : like a thinner
Flash Point : Spray - N/A an airproof can
Consumption : N/A
Cleaner : S 1960
Inflammability : flammable
Solubility in water : non-miscible
Shel Life: : 12 or more months at correct warehousing conditions
Specific weight at 20°C : 0.85g/ml

PACKAGING

300ml spray

CAUTION

Away from children and open fire. Prevent from over heating 50°C.

HEALTH AND SAFETY

This product is classified as extremely flammable (propane-butane)

METHOD OF USING

Clean the surfaces, remove old lubricants by a degreaser S 1960. May be applied by brush or directly sprayed from the can.

The Specified values are average and do not represent specifications.

Manufacturer:: **HF MARKET** s.r.o., Plešnice 25, 330 33 Město Touškov
Czech Republic
Tel: 00420 377 279 255
Fax: 00420 377 279 260
E-mail: hfmarket@hfmarket.cz
technik@hfmarket.cz
www.hfmarket.cz
www.prumyslovalepidla.cz